Multi lane four-side sealing machine
R202V

The new model class which had rapidity, operability and mass production of the powdery four-side sealing package.
The R202 type is a model for the purpose of the mass production that was designed to cut powder, the tegument things in a pouch of the granule with many reams every direction seal.
I perform it continually and, according to the number of the lines, wrap a seal, filling, a slit, a cut.
I could be equipped with the photoelectric tube device and enabled the beautiful finish.
In addition, kind memory was possible and was equipped with bag length variableness, a function of the convenience first including the simple roll cleaning.

R202V

■Specifications

Model	R202V
Packaging style	Four-side sealing
Bag length	45 to 210 mm (Depends on size)
Bag width	From 40 mm in width (500 mm Max.)
Film width	1,040 mm Max.
Packaging speed (*1)	15 to 150 bags/min. (for one lane), 20 m/min. (Depends on film and contents)
Standard devices	•Touch panel •Pattern matching device •Film joint detector •Film brake unit •Film end stop device •Film forward roller •Cutter device •Film shaft moving device(Operated manually) •Product carry out conveyer
Options	•Feeding device(Vasculator, Slide board, Auger) •Printing device(Punch mark, Hot roll, Thermal printer) •Empty bag detecting device •Perforation cutter device •Detective removing device •Dust collector •Edge slit removing device •I Notch device
Power source	3-phase, 200 V, 50/60 Hz
Power consumption (*2)	7.5 kW at peak, 3.5 kW on average
Dimensions	2,060 (W) × 2,350 (D) × 1,950 (H) mm
Air consumption (*2)	0.4 Mpa 100 NL/min.
Weight (*2)	Approx. 2,500 kg

*1: Will be determined at the time of discussing the specifications with you. *2: Varies depending on the specifications.