

FC800 TYPE

FC800



Standard devices

- Temperature monitor
- Film end stop device
- Abnormal air pressure stop device
- Patten matching device
- Edge trimmer air gun
- Total counter
- Preset counter
- Horizontal seal air expelling roller
- Cutter guide
- Slider

SELING POINT OF FC800 "OUR MAXIMUM RESPONSE FOR CUSTOMER'S REQUIREMENT"

- Easy operation of FC series has been kept, and we made our tenancy for simplicity and compact.
- Aiming to suitable size for 4-lane and 6-lane products likely healthy foods and capacity, we realized high efficiency and performance.
- As for option, same options as well as FC1000 are available.
- Maximum line number: 10-lane.

Options

- Vertical seal holder
- Empty bag detector
- Discharge shutter device
- Detection end off packaging film
- Cutter cooling device
- Double hopper
- Hopper net
- Leveler
- Dust collector
- Air gun
- Film joint detector
- Automatic removal device
- Film rear cover
- Film feed motor
- Film horizontal moving motor
- Automatic Vertical seal bar
- Teflon (Funnel, forming pipe)
- Photocell flexible handle
- Edge trimmer motor

Specifications

Model	FC800
Dimensions	1,379 wide × 1,598 deep × 2,500 high mm
Air consumption	0.6 MPa, 650 NL/min.
Weight	Approx. 1,200 kg
Power consumption	7 kw at peak, 4 kw on the average
Dimensions of bag	50 to 190 mm long, 10 to 60 wide, mm (specified dimensions)
Film width	420 mm max.
Packaging speed	20 to 70 bags/min. per line × Number of line