

MR8



- Space saving model.
- MAX. 350 packages/min.
- Product data can be registered under actual product names.

MR8	
Standard functions	* Photocell registration mark control * Film joint detector * Film end detector * Heaters for 2 nd horizontal sealer * Brake unit for film * I-notcher * Cutter * Adjusting device for film position (manual) * Bag top forming rollers * Safety devices (interlocked) * Slide for packages made * Film feeding device with non-slip roller * Adjustable film forming guide.
Storable data	1. Package length 2. Packaging speed 3. Sealing temperature 4. Volume to be filled (No. of rotation – Patent No. 2133529) 5. Registration mark position 6. On/Off of mark control 7. Cutting position 8. Position of perforation cut 9. Position of I-notch 10. No. of perforation cut packages for one strip 11. Printing position 12. Various timings 13. Product names and many others. Storable up to 30 items.
Option	* Perforation cutter * Warning device for film getting scarce * Cover for film station * Automatic discharging device * Divider of packages by preset number * Shutter to accumulate packages by preset number * Preheater for vertical sealer * 4-side sealed package * Tandem package * Intricate bag top seal patterns * Emboss coder * I-notching on both sides * Indicator for film volume * Leakage detector * Detector for product caught between horizontal seal rollers * Nozzle cooling device * Film slitter * Perforation cut on vertical seal * Various date printers * Various pumps * Agitator * UV sterilizer for film * Clean booth * Device to prevent film from meandering * Warning light * Cooling blower * Air compressor * Air drier
Features	<ul style="list-style-type: none"> ◆ Increased operability by adopting a 9.5" single color display. ◆ Little or no gap in registration mark control by having non-slip rollers feed the packaging material. (Result measured by Sanko ± 1mm) ◆ Reliable seals even for packaging oil, vinegar and other foamy products by embedding heaters in the secondary horizontal seal rollers. ◆ Possible to register products by names of products.

Specification

Model	MR8
Ranges of bag length	40~75mm (with 5-up sealing head) / 45~105mm (with 4-up head) 55~160mm (with 3-up head) / 70~210mm (with 2-up head)
Film width	60~ 260mm
Packaging speed	MAX 350bags/min *
Packaging volume	1~150cc **
Diameter of packaging film	MAX : 450
Dimensions	1,230wide × 705deep × 2360high(mm)
Weight	800Kg
Power supply	3-phase,200VAC 50Hz/60Hz (4KW at peak / 2KW on the average)
Air consumption	-

* :Actual packaging speed will vary depending on specifications of the machine, filling volume, physical properties of the film and product to be packaged.

** :Range of filling volume will vary depending on the volume of product discharged from the pump