

# FC-800<sub>TYPE</sub>

## FC-800



### Standard devices

- Temperature monitor
- Film end stop device
- Abnormal air pressure stop device
- Patten matching device
- Edge trimmer air gun
- Total counter
- Preset counter
- Horizontal seal air expelling roller
- Cutter guide
- Slider

## SELING POINT OF FC-800 "OUR MAXIMUM RESPONSE FOR CUSTOMER'S REQUIREMENT"

- Easy operation of FC series has been kept, and we made our tenancy for simplicity and compact.
- Aiming to suitable size for 4 lane and 6 lane products likely healthy foods and capacity, we realized high efficiency and performance.
- As for option, same options as well as FC1000 are available.
- Maximum line number: 10 lines.

### Options

- Virchical seal holder
- Empty bag detector
- Discharge shutter device
- Detection end off packaging film
- Cutter cooling divice
- Double hopper
- Hoppe net
- Leveler
- Dust collector
- Air gun
- Film joint detector
- Automatic removal device
- Film rear cover
- Film feed motor
- Film horizontal moving motor
- Automatic virtical seal bar
- Teflon (Funnel, forming pipe)
- Photocell flexible handle
- Edge trimmer motor

### ●Specifications

Model	<b>FC-800 type</b>
Dimensions	1,379 wide × 1,598 deep × 2,500 high mm
Air consumption	0.6 MPa. 650 NL/min
Weight	Approx. 1,200 kg
Power consumption	7 kw at peak, 4 kw on the average
Bag length	50 to 190 mm long, 10 to 60 mm wide (specified dimensions)
Film width	420 mm max.
Packaging speed	20 to 70 bags/min. per line × Number of line